

# MSDS Report

Applicant's name	Shenzhen Hugnen Technology(HGT) Co ., LTD				
Applicant's Address	B2, Baolihua Industrial Park, Baihua Community, Guangming Shenzhen				
Name of Sample	Polymer Li-ion Battery				
Model	653040				
Nominal Voltage	3.7V				
Rated Capacity	750mAh, 2.775Wh				
Weight	14.6g				
Size (L×W×T)	(41.0×28.3×6.8)mm				
Prepared By	Shenzhen TCT Testing Technology Co., Ltd.  1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.				
Report No.	TCT201116M138				

Written by:	May Hou	Approved by:	Tomsin Lesting Techno
Inspected by:_	Army Zeng	Date: _	2021. 0 TCT

Report No.: TCT201116M138 Page



Section 1- Chemical Product & Company Identification						
Name of Sample	Polymer Li-ion Batter	y				
Manufacturer's name	Shenzhen Hugnen Te	echnology(HC	GT) Co ., LTD			
Manufacturer's Address	B2, Baolihua Industria	al Park, Baihı	ua Community	, Guangming S	Shenzhen	
Contact Person	Mr. Sun					
Tel	+86-755-23420683					
Fax	+86-755-23420686			(C)		
Emergency Tel	+86-755-23420683					
E-mail	sun@hugnen.com		(c1)			

Section 2- Hazards Identification				
Classification of Danger	See section 14.			
Primary Route(s) of Exposure	Eye, skin contact, ingestion.			
Health Hazard	The batteries are not hazardous whe manufacturer under normal condition fire, heat, leakage of internal composincluding but not limited to the following circuited, put into fire, whacked with crushed, and broken.	ons. In case of abuse, the onents, which could caus wing cases: charged for	nere's Hazard of rupture, se casualty loss. Abuses long time, short	



Section 3- Composition/Information on Ingredients				
Chemical Name	Concentration or concentration ranges (%)	CAS Number		
Lithium Cobalt Oxide	15-40	12190-79-3		
Graphite	10-30	7782-42-5		
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3		
Copper	7-13	7440-50-8		
Aluminum foil	5-10	7429-90-5		
Nickel	1-5	7440-02-0		

Labeling according to EC directives.

No symbol and Hazard phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures			
Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.		
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.		
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.		
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.		

Section 5- Fire Fighting Measures				
Characteristics of Hazard	Dusts at sufficient of generates toxic fun		n explosive mixtures with air.	Combustion
Hazardous Combustion Products	Carbon dioxide.	(C)		



Fire-extinguishing Methods and Extinguishing Media	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.
Attention in Fire-extinguishing	Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Measu	ıres
Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7- Handling and Storage			
Handling	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.		
Storage	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.		
Other Precautions	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.		



Section 8 - Exposure Controls/Personal Protection				
Engineering Controls	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m³ respirable fraction (10mg/m³ total) should be observed.			
	Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield.			
Personal Protective Equipment	Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.			
	Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.			

Section 9- Phy	sical and Chemical Properties	
	Appearance: Prismatic	
Physical State	Color: Silver	
(C)	Odour: If leaking, smells of medical ether.	(C)
Change in condit	tion	
pН	Not applicable as supplied.	
Flash Point	Not applicable unless individual components exposed.	
Flammability	Not applicable unless individual components exposed.	
Relative density:	Not applicable unless individual components exposed.	(0)
Solubility (water)	Not applicable unless individual components exposed.	
Solubility (other)	Not applicable unless individual components exposed.	

Section 10 – Stability and Reactivity	
Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Exposure to air or moisture over prolonged periods.



Incompatible materials	Acids, Oxidizing agents, Bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 – Toxicological Information	on
Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization	Not Available.
Reproductive Toxicity	Not Available.
Toxicologically Synergistic Materials	Not Available.

Section 12-Ecological Information	
General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available.

Section 13 – Disposal Considerations	
Waste Treatment	Recycle or dispose of in accordance with government, state & local regulations.
Attention for Waste Treatment	Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

Section 14 – Transport Information		
UN number	3481	
Proper shipping name	Lithium ion batteries contained in equipments (including lithium ion polymer batteries).	
Label(s) / Placard Required	Miscellaneous Lithium batt	



	th a user needs to be aware of, or needs to comply with, in tor conveyance either within or outside their premises
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI)967 Section II appropriate of IATA DGR 62 <sup>nd</sup> (2021 Edition) for transportation.
IMDG CODE:	The batteries are not restricted to IMDG Code 2018 Edition (Amdt 39-18) according to special provision 188.
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2019.

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

### Section 15 - Regulatory Information

**Dangerous Goods Regulations** 

Recommendations on the Transport of Dangerous Goods-Model Regulations (21st revised edition)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG Code 2018 Edition Amdt 39-18)

Technical Instructions for the Safe Transport of Dangerous Goods

Classification and code of dangerous goods (GB 6944-2012)

2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws

Report No.: TCT201116M138 Page 7 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com







#### Section 16 – Additional Information

MSDS creation date: 2021 Version: 1.0

Sample photo:





To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

\*\*\*\*\*\*End of report\*\*\*\*\*

Shenzhen TCT Testing Technology Co., Ltd.

1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

Report Search Number: TCT201116M138

Search System: <a href="http://www.tct-lab.com">http://www.tct-lab.com</a>